



INDIRECT FIRED HEATER
Clean Dry Heat



All the heat you need!

THERMOBILE

Clean And Effective Indirect Heat, Most Efficient System Available!

Powerful fans ensure high static pressure allowing heater placement outdoors with clean dry heated air directed indoors.

Efficient burning as a high pressure pump guarantees full combustion.

High temperature control safety thermostat comes standard.



High efficiency with low fuel consumption.

Easy access filter makes maintenance easier.

Large capacity fuel tank provides a minimum of 17 hours of continuous operation.

Extra handle makes transportation easier.

APPLICATIONS:

Agriculture

- Heating and frost protection of storage areas and workshops.
- Drying of agricultural products.
- Storage of bulbs without the danger of harmful ethylene forming.

Horticulture

- Heating of greenhouses and polytunnels without risk of harmful CO₂ emission.
- Heating of sorting areas.

Industry

- Heating of storage areas, workshops and warehouses.

Construction

- Heating and drying of construction sites and winter projects.

- Built-in reliability and portability.
- Photoelectric flame safety sensor.
- High temperature control thermostat.
- Thermostatically controlled cooling process after shut down.
- Optional thermostat available for constant temperature control.
- Durable powder coated finish.
- Heavy duty wheels and handle provide mobility.
- Grips and protection bar on front side.
- Optional ducting available to direct clean heated air.

Options:



Thermostat RT1



For More Information

DISTRIBUTED BY

Franklin
20 Cedar Street
Franklin, PA 16323

Office: 814.432.4228
Fax: 814.432.4658
Toll Free: 800.533.9870

Cleveland
15151-2 York Road
North Royalton, OH 44133

Office: 440.237.9277
Fax: 440.237.8079
Toll Free: 888.488.9288

Fultz
ENTERPRISES

www.Fultz-Enterprises.com

Specifications:		
Model	ITA 45	ITA 75
Heat output gross (btu/hr)	182,000	240,000
Efficiency	91%	91%
Output (cfm)	1,850	2,350
Duct Diameter ring	16"	16"
Length of ductability (ft.)	60'	40'
Fuel consumption (gal/hr)	1.20	1.85
Tank capacity (gal)	22.3	33.5
Run time on full tank (hr)	17	17
Power required	120/60Hz	120/60Hz
Chimney diameter.	6"	7"
Shipping dimensions (l x w x h)	68" x 27" x 41"	73" x 27" x 46"
Shipping weight (lbs)	332	341