

# CW Series

Electric - Belt Drive Pressure Washer



Mi-T-M® CORPORATION

1. Totally enclosed fan-cooled electric motor with thermal overload protection
2. Belt drive triplex piston pump with ceramic plungers
3. External bypass system creates less heat build-up
4. Forged brass manifold
5. Stainless-steel and brass unloader
6. Thermal relief valve
7. Water filter with clear sleeve for screen inspection
8. Quick-connect nozzles (0°, 15°, 25° and 40°)
9. Heavy-duty dual cogged belt drive system and cast-iron pulleys
10. Totally enclosed powder coated steel belt guard
11. 1/4 inch powder coated steel base plate with powder coated steel tube handles
12. Hose wrap with gun/wand holder
13. Solid steel threaded axle
14. Pneumatic tires with tubes
15. Rubber isolators
16. 3/8 inch x 50 foot non-marking hose with quick connects, swivel and bend restrictors
17. Professional-grade trigger gun with safety lock-off
18. 36 inch steel powder coated lance with rubber grip



CW-2405-4ME1

**Additional features:**

- 10 foot electrical cord (35 foot on CW-2004-1ME1)

Model #	PSI	GPM	HP	Voltage/Phase/Amp	Pump	Unit Dim. (LxWxH)	Ship Wt.	Net Wt.
CW-2004-1ME1 <sup>*</sup>	2000	3.6	5.0	230V/1Ø/21.5	General	40 in. x 32.5 in. x 25.5 in.	259 lbs.	172 lbs.
CW-2004-1ME3 <sup>^</sup>	2000	3.6	5.0	230V/3Ø/14.0 or 460V/3Ø/7.0	General	40 in. x 32.5 in. x 25.5 in.	247 lbs.	160 lbs.
CW-2405-4ME1	2400	4.6	7.5	230V/1Ø/35.7	General	46 in. x 28 in. x 30 in.	347 lbs.	335 lbs.
CW-2405-4ME3 <sup>^</sup>	2400	4.6	8.0	230V/3Ø/24.7 or 460V/3Ø/11.5	General	46 in. x 28 in. x 30 in.	270 lbs.	257 lbs.
CW-3004-4ME1	3000	3.5	7.5	230V/1Ø/35.0	General	46 in. x 28 in. x 30 in.	347 lbs.	335 lbs.
CW-3004-4ME3 <sup>^</sup>	3000	3.5	8.0	230V/3Ø/23.0 or 460V/3Ø/11.5	General	46 in. x 28 in. x 30 in.	270 lbs.	257 lbs.
CW-3005-ØME1	3000	4.8	10.0	230V/1Ø/37.5	General	45.5 in. x 32.5 in. x 30 in.	470 lbs.	329 lbs.
CW-3005-ØME3 <sup>^</sup>	3000	4.8	10.0	230V/3Ø/25.6 or 460V/3Ø/12.8	General	45.5 in. x 32.5 in. x 30 in.	520 lbs.	379 lbs.
CW-3006-4ME3 <sup>^</sup>	3000	5.7	15.0	230V/3Ø/40.0 or 460V/3Ø/20.0	General	45.5 in. x 32.5 in. x 30 in.	556 lbs.	415 lbs.
CW-4004-ØME3 <sup>^</sup>	4000	3.9	15.0	230V/3Ø/40.0 or 460V/3Ø/20.0	General	45.5 in. x 32.5 in. x 30 in.	556 lbs.	415 lbs.
CW-5004-ØME3 <sup>^</sup>	5000	4.0	15.0	230V/3Ø/40.0 or 460V/3Ø/20.0	General	45.5 in. x 32.5 in. x 30 in.	565 lbs.	424 lbs.

<sup>\*</sup>35 foot cord with ground fault circuit interrupter (GFCI).

<sup>^</sup>460V motors available as no-cost options.

DISTRIBUTED BY

**Franklin**  
20 Cedar Street  
Franklin, PA 16323

**Cleveland**  
15151-2 York Road  
North Royalton, OH 44133



Office: 814.432.4228  
Fax: 814.432.4658  
Toll Free: 800.533.9870

Office: 440.237.9277  
Fax: 440.237.8079  
Toll Free: 888.488.9288

[www.Fultz-Enterprises.com](http://www.Fultz-Enterprises.com)

This product information was reproduced and edited by Fultz Enterprises with permission of Mi-T-M Corporation.