

EH Series

Stationary - Electric Pressure Washer



Mi-T-M® CORPORATION

Features:

- Maintains heat after extended use
- Efficient, on demand heat exchanger creates continuous hot water
- Adjustable thermostat
- Automatic on/off controlled at gun
- 20 second delay, preset
- Low inlet pressure (PSI) shutoff
- Fusible plug, temperature sensitive 350°F +/-5°, safety
- Diagnostic control panel
- Hour meter
- Low pressure chemical injection
- Trigger gun control
- Single lance wand with 4 quick connect nozzles nozzle and adjustable soap nozzle
- 3/8 inch x 50 foot high pressure hose with quick connects

All Electric Advantages:

- No refueling
- No ventilation
- No hot exhaust
- No open flame
- No smoke
- No odor



EH-3004-0M30

Note: Electrical cord not included.



Certified
to UL-1776
Standards

Model #	PSI/bar	GPM/lpm	HP	440 Voltage Amps/Kw	575 Voltage Amps/Kw	Outlet Temp (°F/°C)	Unit Dim. LxWxH (in./cm.)	Net Wt. lbs./kg.	Ship Wt. lbs./kg.
<i>EH-2303-0M30</i>	2300/159	3.1/11.7	5.0	51/36	42/36	150°F/66°C	38x21x30/96.5x53.3x76.2	430/195	480/218
<i>EH-3004-0M30</i>	3000/207	3.9/14.8	7.5	98/72	80/72	190°F/88°C	38x21x30/96.5x53.3x76.2	450/218	500/227

DISTRIBUTED BY

Franklin
20 Cedar Street
Franklin, PA 16323

Cleveland
15151-2 York Road
North Royalton, OH 44133

Office: 814.432.4228
Fax: 814.432.4658
Toll Free: 800.533.9870

Office: 440.237.9277
Fax: 440.237.8079
Toll Free: 888.488.9288

www.Fultz-Enterprises.com

Fultz
ENTERPRISES

This product information was reproduced
and edited by Fultz Enterprises with
permission of Mi-T-M Corporation.