

# HHS Series - Standard

Portable - Electric Pressure Washer



Mi-T-M® CORPORATION

## Features:

- Belt drive triplex ceramic plunger pump
- 35 foot power cord with ground fault circuit interrupter (GFCI with 20A plug on 1.5-6.0 H.P., Single phase units)
- 300°F/149°C operating temperature (HHS-303 only)
- Inline fuel filter
- Inlet polyethylene float tank
- Thermal relief valve
- No. 1 or No. 2 fuel oil/diesel/kerosene fired
- 10 gallon polyethylene fuel tank
- Pressure switch and high limit switch safety controls
- Horizontal schedule 80 pipe coil
- Wrinkle finish powder coated steel frame
- Wheel brake
- Wand holder
- (4) 10 inch pneumatic tires with tubes
- Insulated trigger gun
- Adjustable high pressure detergent injection
- Single lance with dual insulated grips; steam nozzle (HHS-303 only)
- Adjustable pressure-insulated dual lance with four quick connect high pressure nozzles (0, 15, 25, 40 degrees) and low pressure nozzle (HHS-1002 - HHS-3004 models)
- 3/8 inch x 50 foot high pressure hose with quick connects



HHS-2004-0E2G



Certified  
to UL-1776  
Standards



Model #	PSI/bar	GPM/lpm	HP	Voltage/ Phase/Amp	Pump	Fuel Cons. (gph/lph)	B.T.U. per hr.	Burner Motor H.P./Volt./Phase	Unit Dim. LxWxH (in./cm.)	Net Wt. lbs./kg.	Ship Wt. lbs./kg.
<b>HHS-1002-0E1G</b>	1000/69	2.0/7.6	1.5	120V/1Ø/16.2	General	1.23/4.66	172,200	1/7/120V/1Ø	57x30x39/144x76x98	455/206	575/261
<b>HHS-1002-0E1A</b>	1000/69	2.0/7.6	1.5	120V/1Ø/16.2	AR	1.23/4.66	172,200	1/7/120V/1Ø	57x30x39/144x76x98	455/206	575/261
<b>HHS-1003-0E1G</b>	1000/69	2.8/10.6	2.0	120V/1Ø/20.0	General	1.84/6.97	257,600	1/7/120V/1Ø	57x30x39/144x76x98	465/211	585/266
<b>HHS-1003-0E1A</b>	1000/69	2.8/10.6	2.0	120V/1Ø/20.0	AR	1.84/6.97	257,600	1/7/120V/1Ø	57x30x39/144x76x98	465/211	585/266
<b>HHS-2004-0E2G</b>	2000/138	4.2/15.9	6.0	230V/1Ø/28.0	General	2.76/10.45	386,400	1/5/230V/1Ø	57x30x39/144x76x98	524/238	644/292
<b>HHS-2004-0E2A</b>	2000/138	4.2/15.9	6.0	230V/1Ø/28.0	AR	2.76/10.45	386,400	1/5/230V/1Ø	57x30x39/144x76x98	524/238	644/292
<b>HHS-2004-0E3G</b>	2000/138	4.2/15.9	6.0	230V/3Ø/18.5	General	2.76/10.45	386,400	1/5/230V/1Ø	57x30x39/144x76x98	524/238	644/292
<b>HHS-2004-0E3A</b>	2000/138	4.2/15.9	6.0	230V/3Ø/18.5	AR	2.76/10.45	386,400	1/5/230V/1Ø	57x30x39/144x76x98	524/238	644/292
<b>HHS-2004-0E4G</b>	2000/138	4.2/15.9	6.0	460V/3Ø/12.0	General	2.76/10.45	386,400	1/5/120V/1Ø	57x30x39/144x76x98	524/238	644/292
<b>HHS-2004-0E4A</b>	2000/138	4.2/15.9	6.0	460V/3Ø/12.0	AR	2.76/10.45	386,400	1/5/120V/1Ø	57x30x39/144x76x98	524/238	644/292
<b>HHS-3004-0E2G</b>	3000/207	3.5/13.2	8.0	230V/1Ø/39.5	General	2.14/8.10	299,600	1/5/230V/1Ø	57x30x39/144x76x98	548/238	668/303
<b>HHS-3004-0E2A</b>	3000/207	3.5/13.2	8.0	230V/1Ø/39.5	AR	2.14/8.10	299,600	1/5/230V/1Ø	57x30x39/144x76x98	548/238	668/303
<b>HHS-3004-0E3G</b>	3000/207	3.5/13.2	8.0	230V/3Ø/22.5	General	2.14/8.10	299,600	1/5/230V/1Ø	57x30x39/144x76x98	548/238	668/303
<b>HHS-3004-0E3A</b>	3000/207	3.5/13.2	8.0	230V/3Ø/22.5	AR	2.14/8.10	299,600	1/5/230V/1Ø	57x30x39/144x76x98	548/238	668/303
<b>HHS-3004-0E4G</b>	3000/207	3.5/13.2	8.0	460V/3Ø/14.0	General	2.14/8.10	299,600	1/5/120V/1Ø	57x30x39/144x76x98	548/238	668/303
<b>HHS-3004-0E4A</b>	3000/207	3.5/13.2	8.0	460V/3Ø/14.0	AR	2.14/8.10	299,600	1/5/120V/1Ø	57x30x39/144x76x98	548/238	668/303
<b>HHS-303-0E1A</b>	300/20.7	2.5/9.5	1.5	120V/1Ø/12.0	AR	2.76/10.45	386,400	1/5/120V/1Ø	57x30x39/144x76x98	455/206	575/261

DISTRIBUTED BY

**Franklin**  
20 Cedar Street  
Franklin, PA 16323

**Cleveland**  
15151-2 York Road  
North Royalton, OH 44133

**Fultz**  
ENTERPRISES

Office: 814.432.4228  
Fax: 814.432.4658  
Toll Free: 800.533.9870

Office: 440.237.9277  
Fax: 440.237.8079  
Toll Free: 888.488.9288

[www.Fultz-Enterprises.com](http://www.Fultz-Enterprises.com)

This product information was reproduced  
and edited by Fultz Enterprises with  
permission of Mi-T-M Corporation.