

# HSE Series

Electric - Belt Drive Pressure Washer



Mi-T-M® CORPORATION

## Features:

- Energy efficient top fired, dual spiral coil with powder coated heat exchanger
- No. 1 or No. 2 diesel or kerosene fired burner
- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- Complete system diagnostic board
- Electric cord hanger
- Belt drive triplex piston pump with ceramic plungers and forged brass manifold
- Stainless-steel and brass unloader valve
- Thermal relief valve
- High pressure detergent injection
- Polyethylene burner fuel tank
- Racor fuel filter/water separator
- 35 ft. power cord (GFCI on HSE-2504-0M10)
- Float tank
- Temperature rise 150°F/66°C maximum above ambient
- Pressure and high limit safety controls
- Solid state electronic ignition
- Wand holder
- Center balanced lifting hook
- Reinforced powder coated steel tube frame
- Easy coil drain
- Pneumatic tires with tubes (4)
- Solid steel threaded axles
- 3/8 inch x 50 foot steel wire-braided pressure hose with screw connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance with 15-degree fixed and detergent nozzles



HSE-3004-0M10



Certified to UL-1776 Standards



Model #	PSI/bar	GPM/lpm	HP	Voltage Phase/Amp	Pump	Burner		Unit Dim. LxWxH (in./cm.)	Ship Wt. lbs./kg.	Net Wt. lbs./kg.
						Tank Cap. (gal/l)	Cons. (gph/lph)			
<b>HSE-2504-0M10</b>	2500/172	3.2/12.1	6.0	208-230V/1Ø/25.0	General	10.0/37.8	2.1/7.95	48.5x28x41/123x74x104	635/290	505/230
<b>HSE-2504-0M30</b>	2500/172	3.2/12.1	6.0	208-230V/3Ø/16.0	General	10.0/37.8	2.1/7.95	48.5x28x41/123x74x104	635/290	505/230
<b>HSE-3004-0M10</b>	3000/207	3.5/13.2	8.0	208-230V/1Ø/36.0	General	10.0/37.8	2.1/7.95	48.5x28x41/123x74x104	660/300	530/240
<b>HSE-3004-0M30</b>	3000/207	3.5/13.2	8.0	208-230V/3Ø/24.0	General	10.0/37.8	2.1/7.95	48.5x28x41/123x74x104	660/300	530/240
<b>HSE-3504-0M10</b>	3500/241	3.3/12.4	10.0	208-230V/1Ø/39.0	General	10.0/37.8	2.1/7.95	48.5x28x41/123x74x104	680/310	550/250
<b>HSE-3504-0M30</b>	3500/241	3.3/12.4	10.0	208-230V/3Ø/28.0	General	10.0/37.8	2.1/7.95	48.5x28x41/123x74x104	680/310	550/250

DISTRIBUTED BY

**Franklin**  
20 Cedar Street  
Franklin, PA 16323

**Cleveland**  
15151-2 York Road  
North Royalton, OH 44133

**Fultz**  
ENTERPRISES

Office: 814.432.4228  
Fax: 814.432.4658  
Toll Free: 800.533.9870

Office: 440.237.9277  
Fax: 440.237.8079  
Toll Free: 888.488.9288

[www.Fultz-Enterprises.com](http://www.Fultz-Enterprises.com)

This product information was reproduced and edited by Fultz Enterprises with permission of Mi-T-M Corporation.