

# HSE Series

Electric - Direct Drive Pressure Washer



Mi-T-M® CORPORATION

## Features:

- Energy efficient top fired, dual spiral coil with powder coated heat exchanger
- No. 1 or No. 2 diesel or kerosene fired burner
- Complete system diagnostic board
- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- Racor fuel filter/water separator
- Polyethylene burner fuel tank
- Direct drive triplex piston pump with ceramic plungers and forged brass manifold
- Thermal relief valve
- Stainless-steel and brass unloader valve
- Float tank (N/A on 1002-0M11)
- High pressure detergent injection (low pressure on 1002-0M11)
- Pressure and high limit safety controls
- Temperature rise 150°F/66°C maximum above ambient
- Easy coil drain
- Solid state electronic ignition
- Reinforced powder coated steel tube frame
- Powder coated center balanced lifting hook
- Electric cord hanger
- Hose reel mounting bracket
- 35 ft. power cord with ground fault circuit interrupter
- Pneumatic tires with tubes (4)
- Solid steel threaded axles
- Wand holder
- 3/8 inch x 50 foot steel wire-braided pressure hose with screw connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance with 15-degree fixed and detergent nozzles



HSE-1502-0M10



Certified to UL-1776 Standards



Model #	PSI/bar	GPM/lpm	HP	Voltage Phase/Amp	Pump	Burner		Unit Dim. LxWxH (in./cm.)	Ship Wt. lbs./kg.	Net Wt. lbs./kg.
						Tank Cap. (gal/l)	Cons. (gph/lph)			
<b>HSE-1002-0M11</b>	1000/69	2.0/7.6	1.5	120V/1Ø/15.0	General	4.0/15.1	1.33/5.0	34x29x33/96.3x73.66x83.8	368/167	245/111
<b>HSE-1002-0M10</b>	1000/69	2.0/7.6	1.5	120V/1Ø/15.0	General	4.0/15.1	1.33/5.0	34x29x33/96.3x73.66x83.8	373/169	250/113
<b>HSE-1502-0M10</b>	1500/103	2.0/7.6	2.0	120V/1Ø/20.0	General	4.0/15.1	1.33/5.0	34x29x33/96.3x73.66x83.8	368/167	255/116
<b>HSE-2003-0M10</b>	2000/138	2.8/10.6	4.0	230V/1Ø/20.0	General	4.0/15.1	1.48/5.6	34x29x33/96.3x73.66x83.8	393/178	273/124

DISTRIBUTED BY

**Franklin**  
20 Cedar Street  
Franklin, PA 16323

**Cleveland**  
15151-2 York Road  
North Royalton, OH 44133

**Fultz**  
ENTERPRISES

Office: 814.432.4228  
Fax: 814.432.4658  
Toll Free: 800.533.9870

Office: 440.237.9277  
Fax: 440.237.8079  
Toll Free: 888.488.9288

[www.Fultz-Enterprises.com](http://www.Fultz-Enterprises.com)

This product information was reproduced and edited by Fultz Enterprises with permission of Mi-T-M Corporation.