

3803VA & 5003VA

Electric Hot Water Pressure Washer



Key Features

- All controls are in one location for easier operation
- Proven pump for intense, long duration uses
- Electronic monitoring of systems
- Pressure up to 2500 psi with 5.5 gpm water flow for the most arduous cleaning tasks (5003VA)
- Max outlet temp of 302°F for an optimum cleaning effect
- Auto Start/Stop allows remote control operation
- KEW ERGO 3000 Spray Gun



PRODUCT

- 03 4 cylinder pump developed for heavy-duty cleaning applications.
- Internal injector for easy application and metering of detergents.
- Temperature of outlet water up to 302°F with steam stage for added versatility.
- Corrosion proof cabinet and rugged frame.
- Storage space for cable, hose and lance.

EASE OF USE

- Acclaimed KEW Technology quick release couplings for inlet hose and high pressure hose.
- Automatic start/stop ensures that the machine only runs when the trigger is squeezed.
- Easy application of detergents with the built-in injector.
- Temperature indicator on control panel.

PRODUCTIVITY

- "Triple-pass" coil ensures the most efficient and economical heating of inlet water. Powerful heating capacity ensures hot water up to 302°F for heavy duty cleaning tasks.
- Designed for quick and easy storage of accessories and equipment, during and after use.

SAFETY

- Hose pressure is relieved when spray gun is released.
- Automatic start/stop reduces wear on pump and motor when not in use.
- Fully enclosed design minimizes exposure to moving and high temperature parts.
- Parking brake and 3 point wheel system prevents rolling.
- Electronic control system ensures maximum security for the user: fuel level, overheating, water flow control, and flame sensor.

ACCESSORIES

- Soda-Blasting (Softblasting)
- Floor Cleaner
- Foam applicator
- Power Rotary Brush
- Tank Cleaner
- Different high pressure hose lengths and lances
- See your KEW® distributor for a complete line of pressure washers and accessories

SPECIFICATIONS

	3803VA	5003VA
Model	3803VA	5003VA
Part No.	6230101	6230147
Pump Pressure	2100 psi	2500 psi
Max Water Flow	5.0 gpm	5.5 gpm
Max Water Temp (inlet)		160°F
Water Temp (Max Flow)		210°F
Water Temp (steam model)		302°F
Fuel Consumption (@194°F)		3.0 gph
Fuel Capacity		10.5 gal
Motor (TEFC)	7.3 hp	8.8 hp
Power (Volt/Amp/Phase)	220/30/1	220/25/3-440/13/3
Automatic Start/Stop		yes
Cord Length		26X ft
Hose Length		50 ft
Lance/Nozzle		Tornado®/065
Dimensions (L x W x H)		54 x 26 x 39 in
Weight	545 lbs	830 lbs

ALTO Cleaning Systems, Inc.
12249 Nations Ford Rd.
Pineville, NC 28134



DISTRIBUTED BY

Franklin
20 Cedar Street
Franklin, PA 16323

Cleveland
15151-2 York Road
North Royalton, OH 44133



Office: 814.432.4228
Fax: 814.432.4658
Toll Free: 800.533.9870

Office: 440.237.9277
Fax: 440.237.8079
Toll Free: 888.488.9288

www.Fultz-Enterprises.com

This product information was reproduced and edited by Fultz Enterprises with permission of ALTO Cleaning Systems, Inc.