

40HA Series

Electric Hot Water Pressure Washers



Key Features

- Automatic start/stop
- Steam cleaning capability
- Available with pressures up to 2100 psi with water flow up to 3.6 gpm
- All controls and couplers are located at one end for simple setup
- On-board electronic self-diagnostic system
- Built-in, adjustable detergent injector and on-board detergent container rack
- Compact design for easy transport
- Accessories and spray lance quick-connect to the spray gun and will swivel under pressure allowing the operator to work from the safest and most efficient position
- KEW ERGO 3000 spray gun



PRODUCT

- Durable CeraTECH pump with brass cylinder head and 3 solid ceramic pistons
- Outlet water temperature up to 302°F for steam cleaning or 194°F for hot water pressure washing
- Rugged, corrosion-proof cabinet
- Built-in burner coil descaling injector
- Ergonomically designed handles and lance for operator convenience and safety
- On-board storage for high pressure hose, lance and power cord

EASE OF USE

- Quick-connectors attach supply and high pressure hoses
- Pressure is adjustable by the operator, at the lance, without tools
- Automatic start/stop ensures that the machine runs only when the spray gun trigger is squeezed
- Large diameter, flat-proof tires and a locking caster for ease of transport
- Built-in detergent injector controlled by the operator at the spray lance, without returning to the machine

PRODUCTIVITY

- "Triple-pass" coil heats water efficiently using less fuel. A single fill-up lasts longer
- Thermostatic control of burner allows selection of the right temperature for the task at hand
- Electronic control system includes service reminder and trouble codes in the event of malfunction

SAFETY

- Flow actuated unloader relieves pressure from the high pressure hose when spray gun is released
- Unloader features an integral overpressure safety valve
- Sturdy cabinet design fully encloses moving and heated parts, minimizing danger of exposure
- 4 sensors monitor and control burner combustion and will stop the machine in the event of an unsafe condition
- 27 ft heavy duty power cord with GFCI (except 3-phase model)

OPTIONS/ACCESSORIES

- 16 in. and 24 in. Floor Cleaner attachments
- Foam Injector and 18 in. or 36 in. Foam Lance
- Super-short (4 in.) and Long (7 ft.) lances
- Powerspeed® VARIO (rotary cleaning nozzle)
- Foam applicator
- Rotary brush
- Tank Cleaner
- Variety of high pressure hose lengths
- Contact your KEW® Distributor for a complete line of available accessories

40HA SERIES ELECTRIC HOT WATER PRESSURE WASHERS

SPECIFICATIONS	0840HA	1840HA	2340HA
Part No	6294021	6295021	6295121
Pump Pressure	1000 psi	1750 psi	2100 psi
Max. Water Volume	2.5 gpm	3.0 gpm	3.6 gpm
Max. Inlet Water Temp.	85° F		
Max. Water Temp.	302°F		
Fuel Consumption	0.9 gph	1.1 gph	1.2 gph
Lance	Tornado - 05*		
Motor H.P.	1.9	3.5	4.4
Power (V/Amps/Phase)	115/18/1	220/18/1	220/22/1
Injector Range	0 - 7 %		
Auto Start/Stop	Yes		
Size (L x W x H)	36 x 26 x 37 in		
Weight	209 lb		



DISTRIBUTED BY

Franklin

20 Cedar Street
Franklin, PA 16323

Office: 814.432.4228
Fax: 814.432.4658
Toll Free: 800.533.9870

Cleveland

15151-2 York Road
North Royalton, OH 44133

Office: 440.237.9277
Fax: 440.237.8079
Toll Free: 888.488.9288



www.Fultz-Enterprises.com

ALTO Cleaning Systems, Inc.
12249 Nations Ford Rd.
Pineville, NC 28134

This product information was reproduced and edited by Fultz Enterprises with permission of ALTO Cleaning Systems, Inc.

