

Scorpion Series

Electric Hot Water Pressure Washers



Key Features

- Machine is designed to be easy to transport and operate
- Models available up to 1600 psi and water flow up to 3.0 gpm
- Consumes up to 50% less fuel than many competitive machines for economical operation



PRODUCT

- Reliable CeraTECH pump with brass cylinder head and 3 ceramic pistons. No oil change required between service intervals
- Rugged, impact resistant, corrosion-proof cabinet and frame
- Ergonomically designed handles for easy transport, with on-board storage for hose and power cord

EASE OF USE

- Quick-couplers and for inlet hose and 50 ft high pressure hose
- User friendly operation with start/stop switch and thermostat on a single panel
- Machine's light weight and large, flat-proof tires make transport easy
- Bayonet-type quick coupler on spray gun allows accessories to be changed easily

PRODUCTIVITY

- 115V and 220V models available
- On-board storage for lance, accessories, high pressure hose and power cord
- Efficient and economical, the thermostatically controlled burner system costs less to operate and allows adjustment of water temperature to match the cleaning application
- KEW ERGO 3000 Spray Gun

SAFETY

- Cabinet design fully encloses moving and heated parts, minimizing danger of exposure
- Low center of gravity protects provides stability in transport
- 35 ft heavy duty power cord with GFCI
- Flow-actuated unloader with integral overpressure safety valve relieves hose pressure while machine is in bypass
- Low burner exhaust temperature

OPTIONS/ACCESSORIES

- Detergent injector
- Water sandblasting and Soda-blasting equipment
- Powerspeed VARIO (rotary-nozzle) lance
- Foam application system
- Rotary brush
- Variety of high pressure hose lengths, and lances
- Contact your KEW® Distributor for a complete line of available accessories

SCORPION SERIES ELECTRIC HOT WATER PRESSURE WASHERS

SPECIFICATIONS	Scorpion	Scorpion	Magnum
Part No	6252021		6255021
Pump Pressure	1100 psi		1600 psi
Max. Water Flow	2.5 gpm		3.0 gpm
Max. Inlet Water Temp.		85° F	
Max. Water Temperature	194°F*		176°F*
Fuel Consumption @ 140°F	0.9 gph		1.1 gph
Lance		Tornado® 05	
Motor H.P.	2.0		3.5
Power (VAC/Amps/Phase)	115/18/1		220/18/1
Size (L x W x H)	36 x 26 x 37 in.		
Weight	230 lb.		239 lb.

* with 54°F inlet water temp.



DISTRIBUTED BY

Franklin
20 Cedar Street
Franklin, PA 16323

Cleveland
15151-2 York Road
North Royalton, OH 44133

Office: 814.432.4228
Fax: 814.432.4658
Toll Free: 800.533.9870

Office: 440.237.9277
Fax: 440.237.8079
Toll Free: 888.488.9288

www.Fultz-Enterprises.com

Fultz
ENTERPRISES

ALTO Cleaning Systems, Inc.
12249 Nations Ford Rd.
Pineville, NC 28134

This product information was reproduced and edited by Fultz Enterprises with permission of ALTO Cleaning Systems, Inc.

ALTO
Group Member