

Uno & Duo Booster



Stationary, Cold Water
Electric Pressure Washer



DURABILITY

KEW's Uno and Duo Boosters are built to handle the toughest cleaning tasks. Whether you have a single user application (Uno) or dual user cleaning requirements (Duo) the Uno and Duo Boosters are designed to operate more than 8 hours a day. A heavy-duty stainless steel cabinet and chassis ensures additional longevity and makes the units easy to clean. Made for high-hygiene applications the Uno & Duo Boosters are ideal for use in the food & beverage industry, pharmaceutical industry, meat processing plants, and much more...



RELIABILITY

The Uno and Duo both come equipped with the renowned KEW C3 pump with 4 ceramic pistons and a low-speed 1400-RPM Totally Enclosed Fan Cooled (TEFC) motor. In addition, the C3 pump allows the use of preheated water up to 160°F enabling these cold-water units to run hot water for degreasing tasks. Over the last 20 years the C3 pump has proven itself to be the most reliable and durable pump on the market, designed to tackle heavy-duty cleaning applications day after day.

USER-FRIENDLINESS AND SERVICEABILITY

Besides being a workhorse the Uno and Duo comes with a load of features making them easy to use and service:

- Visible oil level indicator
- Easy to use start/stop button
- Low water security function
- Stainless steel valves
- Brass cylinder head
- Closed oil system
- Integrated flow sensor for dry run protection
- Pump head with integrated filter
- Powerful integrated motor with dual thermo sensors
- Integrated LCD control for easy troubleshooting
- Automatic start stop function will turn off the unit after 30 sec. inactivity and will restart the pressure washer by simply squeezing the trigger!



VERSATILITY

KEW offers an extensive line of accessories to compliment our industrial pressure washers. Knowledgeable KEW trained field engineers provide on-site applications expertise and prompt local service.



UNO & DUO SPECIFICATIONS

Model	Uno (Single Pump)	Uno (Single Pump)	Duo (Dual Pump)
Part No.	107340123 (1x220V)	107340122 (3x220V) 107340124 (3x460V)	107340322 (3x220V) 107340323 (3x460V)
Pump Pressure	2200 PSI	2600 PSI	2600 PSI
Max Water Flow	5.0 GPM	5.5 GPM	5.5 - 11.0 GPM
Max Inlet Temp.		160 F	
Motor H.P.	7.3	7.5	2x8.8
Power (Phase/V./A.)	1/220/29	3/220/21 & 3/460/12	3/220/& 3/460/24
Automatic Start/Stop		Yes	
Nozzle Size		Tornado 2506	
Size (L x W x H)	28 x 16 x 28		28 x 16 x 39 1/2
Weight	179 Lbs		353 Lbs

ALTO Cleaning Systems, Inc.
12249 Nations Ford Rd.
Pineville, NC 28134

DISTRIBUTED BY

Franklin
20 Cedar Street
Franklin, PA 16323

Cleveland
15151-2 York Road
North Royalton, OH 44133



Office: 814.432.4228
Fax: 814.432.4658
Toll Free: 800.533.9870

Office: 440.237.9277
Fax: 440.237.8079
Toll Free: 888.488.9288

www.Fultz-Enterprises.com



This product information was reproduced and edited by Fultz Enterprises with permission of ALTO Cleaning Systems, Inc.