

Attix 12 AS/PE EC Critical Applications Vacuum



The Attix 12 AS/PE EC vacuum is powered by a spark less, brush less, electronically-controlled motor. No spark means it is suitable for use in hazardous areas where ignition sources are prohibited.

Features

- No carbon particles from motor brushes in the vacuum exhaust
- Ambient air is filtered before passing through motor-cooling duct
- SoftStart motor prevents power peaks and voltage breakdowns, extending service life up to 10 times as long as conventional motor
- Designed for use with pneumatic or electric power tools
 - AutoStart circuitry allows vacuum power to be remotely controlled by the operator from the connected tool
 - Anti-static hose



Includes:

- Washable, one-micron fleece filter
- 1 1/4" x 16' anti-static suction hose
- Lockable containment bag
- Auxiliary electrical outlet (110 Volt)



Technical Data:

- 57 dB(A) sound level
 - 1.6 HP motor
 - 140 CFM (air flow)
- 105" static water lift
 - 53 lbs

DISTRIBUTED BY

Franklin
20 Cedar Street
Franklin, PA 16323

Cleveland
15151-2 York Road
North Royalton, OH 44133

Office: 814.432.4228
Fax: 814.432.4658
Toll Free: 800.533.9870

Office: 440.237.9277
Fax: 440.237.8079
Toll Free: 888.488.9288

Fultz
ENTERPRISES

www.Fultz-Enterprises.com