

Drum-Top Vacuum Features & Benefits

Fits on a standard 55-gallon, open-top drum you supply.
Great for continuous clean-up operations.

FEATURES:

- Auto Start/Stop
- SoftStart
- Power Regulator
- 140 CFM Air Flow, 105-Inch Water Lift
- XtremeClean Filter Cleaning System
- Fleece Filter
- HEPA Filter (Optional)
- 13-Foot Crush-Proof Hose
- Optional Drum Dolly



BENEFITS:

Users can activate the machine automatically when used in conjunction with electric and/or pneumatic tools

Prevents voltage breakdowns by keeping starting current low

To adjust suction performance, preventing the tool from sticking to the work surface

Very powerful suction performance

Filter cartridge cleans itself automatically. One half of the filter chamber gets blown off while the other half is used to vacuum. A sensor monitors the airflow in both chambers and reverses the procedure when necessary. This patented feature eliminates the use of conventional filter bags and triples the life of the filter cartridge.

Plastic-coated fleece filter to allow use with wet *and* dry substances without a filter change

Filters down to 0.3 microns; meets and exceeds OSHA, EPA and DOD standards

Longer length for cleaning ease, very flexible, heavy-duty hose for the roughest environments

Industrial-grade dolly adds portability. Holds up to 800 lbs.

This product information was reproduced and edited by Fultz Enterprises with permission of Alto Cleaning Systems, Inc.

DISTRIBUTED BY

Franklin
20 Cedar Street
Franklin, PA 16323

Cleveland
15151-2 York Road
North Royalton, OH 44133

Office: 814.432.4228
Fax: 814.432.4658
Toll Free: 800.533.9870

Office: 440.237.9277
Fax: 440.237.8079
Toll Free: 888.488.9288

Fultz
ENTERPRISES

www.Fultz-Enterprises.com